

3940P2Ti

Pistol Grip Titanium Impact Tool

Twin Hammer Mechanism [●]

is the strongest, most durable, longest life mechanism in the industry.



increases strength, reduces weight, and provides exceptional corrosion resistance.

Laser-etched [] -

product information lasts the life of the tool.


Integrated Muffler [●] -

is protected from rough handling.

MODEL	3940P2Ti
Drive Size	1" square
Free Speed	5,300 rpm
Impacts Per Minute	800
Max Torque Reverse	2,750 ft-lb (3730 Nm)
Max Torque Forward	2,500 ft-lb (3390 Nm)
Torque Range Reverse*	500 – 1,800 ft-lb (680 – 2440 Nm)
Torque Range Forward*	500 - 1,650 (680 - 2240 Nm)
Weight, Less Socket	20.4 lb (9.3 kg)
Length, Less Socket	10.1" (256 mm)
Side To Center	2.3" (59 mm)
Recommended Hose Size	3/4" (19 mm)
Air Consumption	75 cfm
+D 1 1 10 11	

*Recommended specifications.

Distributed by:



[•] Bronze Endplates for the ultimate in corrosion and wear resistance.

[•] Integrated Reverse Lever provides protection in the most abusive applications.

[•] Ergonomic
Pistol Grip Handle
improves operator comfort.

Ingersoll-Rand offers an extended two-year warranty program for the impact mechanism with the purchase of the Ingersoll-Rand extended warranty kit. The extended warranty kit includes a hose whip with swivel, inline lubricator, two couplers, oil, grease, and titanium gloves.

MODEL	DESCRIPTION
3900-XW1-M	2-year Extended Warranty Kit for impact mechanism with medium gloves
3900-XW1-L	2-year Extended Warranty Kit for impact mechanism with large gloves
3900-XW1-XL	2-year Extended Warranty Kit for impact mechanism with extra large gloves

